

SPECIFICATION SHEET

HPF SERIES HC416-PP Water Filtration

Single Manifold Part #:**300-651**Replacement Cartridge:**HC416-PP**



APPLICATIONS







Steamers/ Coffee/Tea Combi-oven

Espresso/ Cappuccino

Ice Machine

- Volume: Low-Medium
- 1 Carbonator

DESIGNED TO

- Improve taste, aroma, & clarity of brewed beverages while removing disinfectants and contaminants
- Maintain recipe compliance and deliver a consistent beverage experience
- Reduce scale formation and pitting to prolong equipment life
- Reduce chlorine, undesirable taste & odor, class 1 particulates and sediment

PERFORMANCE

Chlorine Capacity	40,000 gal @ 2.5 gpm
Scale Reduction	Up to 40,000 gal @ 2.5 gpm
Min./Max. Pressure	20 - 125 psi
Min./Max. Temp.	40°- 100°F
Inlet/Outlet Size	3/4" FNPT
Shipping Weight	4 lb
Dimensions (W/D/H)	10" x 5.5" x 19.5"

Performance may vary based on local water conditions

FEATURES & BENEFITS

- Activated hollow carbon with NO binding agent delivers high capacities, high flow rates, and minimal pressure drop in a compact solution
- Engineered polymer construction for high durability and extended service life
- Modular design allows for easy capacity expansion
- Time released polyphosphate increases protection of equipment from scale build up



1.800.321.5022 www.KineticoPRO.com WaterCare@KineticoPRO.com



Tested and certified by NSF International against NSF/ANSI Standard 42 for the reduction of Chlorine, Taste & Odor and Particulate Class I.