

NanoSmart™ SERIES KPMF HC610-MP Water Filtration

Single Manifold Part #: **KP-300-777**
Replacement Cartridge: **KPMF HC610-MP**



APPLICATIONS



Fountain



Coffee/Tea



Juice



Drinking water

- 1 Carbonator
- Volume: Low-Medium

DESIGNED TO

- Improve taste of fountain beverages
- Provide clean ingredient water to your operations
- NanoSmart™ technology helps to remove undesirable impurities including bacteria, delivering exceptional water quality.
- Reduce chlorine, undesirable taste & odor, class 1 particulates, cysts* and sediment

PERFORMANCE

Chlorine Capacity	50,000 gal @ 4 GPM
Micron Rating	1
Min./Max. Pressure	40 - 100 psi
Min./Max. Temp.	40°- 100°F
Inlet/Outlet Size	3/4" FNPT
Shipping Weight	13 lb
Dimensions (W/D/H)	14" x 9" x 19"

Performance may vary based on local water conditions
EPA Est. No. 92879-GA-1

*Tested by 3rd party laboratory to the NSF/ANSI Standard 42

FEATURES & BENEFITS

- 100% activated, hollow carbon with no binding agent delivering high capacities and flow rates with minimal pressure drop
- NanoSmart technology utilizes electro-adsorptive material designed to help reduce microbial contaminants and chemicals
- Turbo Flow technology evenly distributes water flow and helps to reduce plugging
- Engineered polymer construction for high durability and extended service life
- Modular design allows for easy capacity expansion



Tested and certified by NSF International against NSF/ANSI Standard 42 for the reduction of Chlorine, Taste & Odor and Particulate Class I.

NanoSmart™ SERIES KPMF HC614-MP Water Filtration

Single Manifold Part #: **KP-300-777**
Replacement Cartridge: **KPMF HC614-MP**



APPLICATIONS



Fountain



Coffee/Tea



Juice



Drinking water

- 1 to 2 Carbonator
- Volume: Medium

DESIGNED TO

- Improve taste of fountain beverages
- Provide clean ingredient water to your operations
- NanoSmart™ technology helps to remove undesirable impurities including bacteria, delivering exceptional water quality.
- Reduce chlorine, chloramine*, undesirable taste & odor, class 1 particulates, cysts* and sediment

PERFORMANCE

Chlorine Capacity	75,000 gal @ 6 GPM
Chloramine Capacity	5,200 gal @ 1.7 GPM*
Micron Rating	1
Min./Max. Pressure	40-100 psi
Min./Max. Temp.	40° - 100°F
Inlet/Outlet Size	3/4" FNPT
Shipping Weight	15 lb
Dimensions (W/D/H)	14" x 9" x 23"

Performance may vary based on local water conditions
EPA Est. No. 92879-GA-1

* Tested by 3rd party laboratory to the NSF/ANSI Standard 42

FEATURES & BENEFITS

- 100% activated, hollow carbon with no binding agent delivering high capacities and flow rates with minimal pressure drop
- NanoSmart technology utilizes electro-adsorptive material designed to help reduce microbial contaminants and chemicals
- Turbo Flow technology evenly distributes water flow and helps to reduce plugging
- Engineered polymer construction for high durability and extended service life
- Modular design allows for easy capacity expansion