HC SERIES KPMF HC620-PFAS Water Filtration

Single Manifold Part #: **KP-300-777** Replacement Cartridge: **KPMF HC620-PFAS**

14"



29"



APPLICATIONS









Drinking water

Fountain

Coffee/Tea

DESIGNED TO

- Reduce PFOS/PFOA from water supply.
- Reduce chlorine, chloramine, taste & odor, class 1 particulates, and sediment.
- Provide clean ingredient water to your facility while improving taste and a reduction of undesirable odors.

PERFORMANCE

PFOS/ PFOA Capacity	5,700 gal @ 2.8GPM
Chlorine Capacity	5,700 gal @ 2.8GPM
Chloramine Capacity	5,700 gal @ 2.8GPM
Min./Max. Pressure	40-100 psi
Min./Max. Temp.	40°- 100°F
Inlet/Outlet Size	3/4" FNPT
Shipping Weight	17 lb
Dimensions (W/D/H)	14" x 9" x 29"

Performance may vary based on local water conditions

FEATURES & BENEFITS

- 100% binder-free activated Hollow Carbon maximizes performance for longer cartridge life.
- Offers a uniquely engineered, ultra high-porosity catalytic carbon providing an extraordinarily large active surface area.
- Turbo Flow technology evenly distributes water flow and helps to reduce plugging.
- Engineered polymer construction for high durability and extended service life
- Modular design allows for easy capacity expansion.



System tested and certified by NSF International against NSF/ANSI Standard 42 and CSA B483.1 for the reduction of Chlorine, Chloramine, Taste & Odor, Particulate Class I and NSF/ANSI Standard 53 for PFOS/PFOA.