CoffeePRO SERIES KPMF CP620-PP Water Filtration

Single Manifold Part #: KP

KP-300-777

29"

Replacement Cartridge: KPMF CP620-PP

14"





APPLICATIONS





Coffee/Tea

Espresso/ Cappuccino

- · Volume: High
- Optimal for Multi-Brewer

DESIGNED TO

- Improve taste, aroma, & clarity of brewed beverages
- Maintain recipe compliance and deliver a consistent beverage experience
- Reduce scale formation and pitting to prolong equipment life
- Remove disinfectants and contaminants, providing high quality ingredient water

PERFORMANCE

Chlorine Capacity	100,000 gal @ 10gpm
Chloramine Capacity	35,000 gal @ 1.7gpm
Scale Reduction	Up to 100,000 gal @ 10gpm
Min./Max. Pressure	40 - 100 psi
Min./Max. Temp.	40°- 100°F
Inlet/Outlet Size	3/4" FNPT
Shipping Weight	18 lb
Dimensions (W/D/H)	14" x 9" x 29"

Performance may vary based on local water conditions

FEATURES & BENEFITS

- Activated hollow carbon with NO binding agent delivers high capacities, high flow rates, and minimal pressure drop
- Engineered polymer construction for high durability and extended service life
- Modular design allows for easy capacity expansion
- Time released polyphosphate increases protection of equipment from scale build up



Tested and certified by NSF International against NSF/ANSI Standard 42 for the reduction of chlorine, chloramine, particulate class I, and taste & odor.