



CoffeePRO Series

SMF CoffeePRO 600

Water Filtration

System Part #: **80-6100CP**
 Replacement Cartridge: **108-010CP**



APPLICATIONS



Coffee/Tea



Espresso/
Cappuccino

- Volume: Low-Medium
- Optimal for Single or Multi-Brewer

DESIGNED TO

- Improve taste, aroma, & clarity of brewed beverages
- Maintain recipe compliance and deliver a consistent beverage experience
- Reduce scale formation and pitting to prolong equipment life
- Remove disinfectants and contaminants, providing high quality ingredient water

PERFORMANCE

Chlorine Capacity	50,000 gal @ 5gpm
Chloramine Capacity	7,150 gal @ 1.7gpm*
Scale Reduction	Up to 50,000 gal @ 5gpm
Min./Max. Pressure	40 - 100 psi
Min./Max. Temp.	40°- 100°F
Inlet/Outlet Size	3/4" FNPT
Shipping Weight	15 lb
Dimensions (W/D/H)	14" x 9" x 19"

Performance may vary based on local water conditions

*Tested by 3rd party laboratory to the NSF/ANSI Standard 42

FEATURES & BENEFITS

- Activated hollow carbon with NO binding agent delivers high capacities, high flow rates, and minimal pressure drop
- Engineered polymer construction for high durability and extended service life
- Modular design allows for easy capacity expansion
- Time released polyphosphate increases protection of equipment from scale build up



Tested and certified by NSF International against NSF/ANSI Standard 42 for the reduction of chlorine, particulate class I, and taste & odor.