

CLM SERIES

KPMF CLM620

Water Filtration

Single Manifold Part #: **KP-300-777**
Replacement Cartridge: **KPMF CLM620**



APPLICATIONS



Fountain



Coffee/Tea



Espresso/
Cappuccino



Steamers/
Combi-oven

- Optimal for ultrahigh chloramine centric markets
- Volume: High

DESIGNED TO

- Deliver superior reduction of both chloramine and chlorine, reducing off-tastes and foul odors
- Provide clean ingredient water to your operations to help maintain ongoing recipe compliance
- Reduce chlorine, chloramine, taste & odor, class 1 particulates, and sediment

PERFORMANCE

Chloramine Capacity	60,000 gal @ 2.5GPM
	45,000 gal @ 3.4GPM
Chlorine Capacity	100,000 gal @ 10 GPM
Micron Rating	1
Min./Max. Pressure	40 - 100 psi
Min./Max. Temp.	40°- 100°F
Inlet/Outlet Size	3/4" FNPT
Shipping Weight	20 lb
Dimensions (W/D/H)	14" x 9" x 29"

Performance may vary based on local water conditions

FEATURES & BENEFITS

- Ultra catalytic carbon delivers superior chloramine and chlorine removal while sustaining high flow rates.
- Compatible with any double, triple and quad KPMF/SMF manifold system
- Delivers optimal taste and clarity of your company's fountain and tea/ coffee beverage specifications to enhance guest satisfaction
- Turbo Flow technology evenly distributes water flow and helps to reduce plugging
- Engineered polymer construction for high durability and extended service life



Tested and certified by NSF International against NSF/ANSI Standard 42 for the reduction of Chlorine, Chloramine, Taste & Odor and Particulate Class I.