

CoffeePRO SERIES

KPMF CP620-PP

Water Filtration

Single Manifold Part #: **KP-300-777**
Replacement Cartridge: **KPMF CP620-PP**



APPLICATIONS



Coffee/Tea



Espresso/
Cappuccino

- Volume: High
- Optimal for Multi-Brewer

DESIGNED TO

- Improve taste, aroma, & clarity of brewed beverages
- Maintain recipe compliance and deliver a consistent beverage experience
- Reduce scale formation and pitting to prolong equipment life
- Remove disinfectants and contaminants, providing high quality ingredient water

PERFORMANCE

Chlorine Capacity	100,000 gal @ 10gpm
Chloramine Capacity	35,000 gal @ 1.7gpm
Scale Reduction	Up to 100,000 gal @ 10gpm
Min./Max. Pressure	40 - 100 psi
Min./Max. Temp.	40° - 100°F
Inlet/Outlet Size	3/4" FNPT
Shipping Weight	18 lb
Dimensions (W/D/H)	14" x 9" x 29"

Performance may vary based on local water conditions

FEATURES & BENEFITS

- Activated hollow carbon with NO binding agent delivers high capacities, high flow rates, and minimal pressure drop
- Engineered polymer construction for high durability and extended service life
- Modular design allows for easy capacity expansion
- Time released polyphosphate increases protection of equipment from scale build up
- Certified by NSF for microplastic reduction. These refer to small pieces of plastic from packaging, microbeads, plastic bottles, bags, and more



System Tested and Certified by NSF International against NSF/ANSI Standards 42 for reduction of Chlorine, Taste and Odor; Particulate Reduction, Class I (0.5-1.0 micron), NSF/ANSI Standard 401 for the reduction of Microplastics, and CSA Standard B483.1.