

# KPMF SERIES

## KPMF CLM620

### Water Filtration

Single Manifold Part #: **KP-300-777**  
Replacement Cartridge: **KPMF CLM620**



### APPLICATIONS



Fountain



Coffee/Tea



Espresso/  
Cappuccino



Steamers/  
Combi-oven

- Optimal for Chloramine centric markets
- Volume: High

### DESIGNED TO

- Deliver superior reduction of both Chloramine and Chlorine, reducing off-tastes and foul odors
- Provide clean ingredient water to your operations to help maintain ongoing recipe compliance
- Reduce chlorine, chloramine, taste & odor, class 1 particulates, and sediment

### PERFORMANCE

Chloramine Capacity	<b>60,000 gal @ 2.5GPM</b> <b>45,000 gal @ 3.4GPM</b>
Chlorine Capacity	<b>100,000 gal @ 10 GPM</b>
Micron Rating	<b>1</b>
Min./Max. Pressure	<b>40 - 100 psi</b>
Min./Max. Temp.	<b>40°- 100°F</b>
Inlet/Outlet Size	<b>3/4" FNPT</b>
Shipping Weight	<b>20 lb</b>
Dimensions (W/D/H)	<b>14" x 9" x 29"</b>

Performance may vary based on local water conditions

### FEATURES & BENEFITS

- Innovative water filtration design delivers superior chloramine and chlorine removal while sustaining high flow rates.
- Compatible with any double, triple and quad KPMF/SMF manifold system
- Delivers optimal taste and clarity of your company's fountain and tea/ coffee beverage specifications to enhance guest satisfaction
- Turbo Flow technology evenly distributes water flow and helps to reduce plugging
- Engineered polymer construction for high durability and extended service life



Tested and certified by NSF International against NSF/ANSI Standard 42 for the reduction of Chlorine, Chloramine, Taste & Odor and Particulate Class I.